

## PRODUCT DATA SHEET

### envirofloor oak HERRINGBONE



#### COLOUR SELECTION



#### PRODUCT DETAILS

Product range	Herringbone
Species	European Oak
Timber origin	France
Veneer	3mm
Thickness	14mm
Width	90mm-150mm
Length	450mm-900mm
Nesting	No
Pack size	TBA
Timber grade	ABC
Construction	Engineered
Substrate	Cross laminated plantation eucalyptus
Profile	T/G
Finish	acrylic lacquer
Surface	brushed open coating
Sheen level	less than 10%
Edge profile	micro-bevel
Glue	MUF
Responsible timber certification	Yes

#### MAINTENANCE

Timber floor care apply, full care and maintenance instructions are available at [auswood.com.au](http://auswood.com.au)

#### WARRANTY

Structure	Lifetime
Surface wear	Domestic: 25 years Commercial: 5 years

Full Warranty Terms & Conditions are available at [auswood.com.au](http://auswood.com.au)

#### PERFORMANCE

Formaldehyde Emission	E0	
VoC	Greengard Gold Certificate UL 2818 - 2013	
Slip Resistance	P3	AS 4586:2013
Fire Rating – CFH value	4.7 kw/m <sup>2</sup>	AS/ISO 9239.1-2003
Fire Rating – Smoke Value	7% min	AS/ISO 9239.1-2003

#### TIMBER GRADE

ABC mix grade average characters

Average character grade typically may include knots in limited size, minor cracks across growth ring, color variation and heartwood. Filler may be used in finish.

#### INSTALLATION

Floating on subfloor	No
Nailing	No
Fully bonding	Yes – Recommended
Under Floor Heating	Yes* (conditions apply)

Full installation instructions are available at [auswood.com.au](http://auswood.com.au)

\*Under Floor Heating guidelines: Set under floor heating system to max 37°C and keep room temperatures about 18°C to 24°C with optimum relative humidity range between 45% and 60%

