



STOCKMANS RIDGE PREMIUM
AUSTRALIAN SPECIES TIMBER



Stockmans Ridge Premium | Spotted Gum

CARPET COURT

AUSTRALIAN HARDWOOD THAT'S MORE FASHIONABLE AND ATTRACTIVE



Blackbutt



Sydney Blue Gum



Spotted Gum



Jarrah

FEATURES

2.5mm thick veneer as an ultimate solution allowing re-sanding with free of mind.

Brushed surface highlighting texture and features representing unique beauty and elegance of Australian hardwood.

Increased stability from de-stressed veneer and balanced structure reducing the opportunity of cupping and surface checking.

CARE AND MAINTENANCE

Proper care and maintenance will help to keep your Stockmans Ridge Premium floor looking as new as possible.

PROTECTION

Use normal timber floor protection such as floor rugs and doormats to avoid wear damage and scratches to your new flooring surface.

Timber floors will darken with exposure to light. Move rugs and mats regularly to avoid patches of different colours.

CLEANING AND MAINTENANCE

Regular sweeping and cleaning with Bona products is highly recommended. A wide range of Bona flooring maintenance products can be purchased from your local Carpet Court Store.

RE-SANDING AND RE-COATING

Due to its specially designed structure and high stability, Stockmans Ridge Premium flooring will retain a flat surface for its lifetime. Should re-coating be required, use a buffing pad to rough up existing coating on the whole Stockmans Ridge Premium range. Fine grit sanding paper can be used on Stockmans Ridge Premium flooring to remove existing coating. Always seek advice from your supplier about the most appropriate re-coating process.

SPECIFICATIONS

SPECIES	Blackbutt, Sydney Blue Gum, Spotted Gum, Jarrah
VENEER	2.5mm face veneer thickness
SUBSTRATE	Cross-laminated plantation Eucalyptus
SIZES	1830 x 186 x 15/2.5mm
CLICK	Patented Välinge click locking system
FINISH	Acrylic finish with special dent and scratch resistance technology
WARRANTY	25 year domestic or 5 year commercial warranty
STANDARDS	Manufactured to meet globally recognised standards: ASTM D-2394; ASTM D-3359 and ASTM D-4060
PACKING	186mm wide – 6 pieces covering 2.042m ² per carton. 50 cartons or 102.114m ² per pallet
NESTING	15/2.5mm thickness: up to 2/6 of 600, 900 or 1200mm



AUSWOOD INTERNATIONAL PTY LTD

P 02 9792 8986

E enquiries@stockmansridgeflooring.com.au

www.stockmansridgeflooring.com.au

www.auswood.com.au

NB: Swatches are only indicative of colour and should be used as a guide only. Current as of April 2019. As timber is a natural material a vast degree of variety in colour, texture and naturally occurring feature can be found. Ranges may vary from store to store. Please contact your nearest store for more information.