

PRODUCT DATA SHEET

envirofloor premium



COLOUR SELECTION



PRODUCT DETAILS

Product range	envirofloor premium
Species	Selected Australian or exotic hardwood
Timber origin	Australia or Pacific Islands
Veneer	3mm
Thickness	15mm
Width	136 or 186mm
Length	1830mm
Nesting	Up to 2/6
Pack size	TBA
Timber grade	Standard and better
Construction	Engineered
Substrate	Cross laminated plantation eucalyptus
Profile	Valinge 2G click locking
Finish	acrylic lacquer
Surface	Brushed semi-closed coating
Sheen level	less than 10%
Edge profile	micro-bevel
Glue	MUF
Responsible timber certification	Yes

MAINTENANCE

Timber floor care apply, full care and maintenance instructions are available at auswood.com.au

WARRANTY

Structure	Lifetime
Surface wear	Domestic: 25 years Commercial: 5 years

Full Warranty Terms & Conditions are available at auswood.com.au

PERFORMANCE

Formaldehyde Emission	E0
VoC	Greengard Gold Certificate UL 2818 - 2013
Slip Resistance	P3 AS 4586:2013
Fire Rating – CFH value	4.7 kw/m ² AS/ISO 9239.1-2003
Fire Rating – Smoke Value	7% min AS/ISO 9239.1-2003

TIMBER GRADE

Standard and better

standard and better grade means typical feature included in limited size and range depends on timber species.

INSTALLATION

Floating on subfloor	Yes
Nailing	Yes
Fully bonding	Yes
Under Floor Heating	Yes* (conditions apply)

Full installation instructions are available at auswood.com.au

*Under Floor Heating guidelines: Set under floor heating system to max 37°C and keep room temperatures about 18°C to 24°C with optimum relative humidity range between 45% and 60%



CONTACT